



GTF 1000

Products

Illustration and dimensioned drawing	Article description	Pressure connection	Article #																
	<p>Submersible pump GTF 1000 for wastewater without sewage with/without float switch Connection to pressure pipe 1 1/4 inch. Outlet side / vertical, without macerator, cable length 10 m</p> <p>1 without float switch 2 with float switch</p> <p>Voltage: 230 V ~ 50 Hz Input power (P1): 1080 W Max. pumping height: 10 m Max. pumping capacity: 11,5 m³/h Max. submersible depth: 10 m Max. particle size: 10 mm Pressure connection: 1 1/4 inch side / vertical</p>	1 1 1/4 inch	28 760																
		2 1 1/4 inch	28 860																
			<table border="1"> <thead> <tr> <th colspan="2">GTF 1000</th> </tr> </thead> <tbody> <tr> <td>Current type</td> <td>Alternating current</td> </tr> <tr> <td>Voltage</td> <td>230 V</td> </tr> <tr> <td>Current</td> <td>4.9 A</td> </tr> <tr> <td>Power P1/P2</td> <td>1080 W / 620 W</td> </tr> <tr> <td>RPM</td> <td>2800 min⁻¹</td> </tr> <tr> <td>Motor protection</td> <td>integrated</td> </tr> <tr> <td>Operating mode</td> <td>S3 - 30 %</td> </tr> </tbody> </table>	GTF 1000		Current type	Alternating current	Voltage	230 V	Current	4.9 A	Power P1/P2	1080 W / 620 W	RPM	2800 min ⁻¹	Motor protection	integrated	Operating mode	S3 - 30 %
GTF 1000																			
Current type	Alternating current																		
Voltage	230 V																		
Current	4.9 A																		
Power P1/P2	1080 W / 620 W																		
RPM	2800 min ⁻¹																		
Motor protection	integrated																		
Operating mode	S3 - 30 %																		

KTP 500

Products

Illustration and dimensioned drawing	Article description	Pressure connection	Article #																
	<p>Submersible pump KTP 500 / KTP 500 TITAN for wastewater without sewage with/without float switch Connection to pressure pipe 1 1/4 inch. Outlet side / vertical, cable length 10 m</p> <p>1 without float switch 2 with float switch</p> <p>Voltage: 230 V ~ 50 Hz Input power (P1): 480 W Max. pumping height: 8 m Max. pumping capacity: 8 m³/h Max. submersible depth: 10 m Max. particle size: 10 mm Pressure connection: 1 1/4 inch side / vertical</p> <p>Special model with titanium shaft Suitable for mechanical and chemical polluted media. Also resistant to chloride-containing media. Not to be used for nitro- and trichloroethylene</p>	KTP 500																	
		1 1 1/4 inch	28 710																
		2 1 1/4 inch	28 810																
		KTP 500 TITAN																	
		1 1 1/4 inch	28 750																
		2 1 1/4 inch	28 850																
			<table border="1"> <thead> <tr> <th colspan="2">KTP 500</th> </tr> </thead> <tbody> <tr> <td>Current type</td> <td>Alternating current</td> </tr> <tr> <td>Voltage</td> <td>230 V</td> </tr> <tr> <td>Current</td> <td>2.12 A</td> </tr> <tr> <td>Power P1/P2</td> <td>480 W / 320 W</td> </tr> <tr> <td>RPM</td> <td>2800 min⁻¹</td> </tr> <tr> <td>Motor protection</td> <td>integrated</td> </tr> <tr> <td>Operating mode</td> <td>S1</td> </tr> </tbody> </table>	KTP 500		Current type	Alternating current	Voltage	230 V	Current	2.12 A	Power P1/P2	480 W / 320 W	RPM	2800 min ⁻¹	Motor protection	integrated	Operating mode	S1
KTP 500																			
Current type	Alternating current																		
Voltage	230 V																		
Current	2.12 A																		
Power P1/P2	480 W / 320 W																		
RPM	2800 min ⁻¹																		
Motor protection	integrated																		
Operating mode	S1																		