

Variofix Classic bathroom drain GI fl., DN 70, vert., slot grat., K3



Article information

Item no.: 40279.50
GTIN: 4026092029602
Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant

Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Adhesive flange (suitable for moisture barriers)
Water supply:	W3-I
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm backwater:	0,8

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	70
Outer diameter (OD):	75 mm

Dimensions

Vertical adjustment:	55 - 120 mm
Net weight:	1,44 kg
Gross weight:	2,07 kg
Cutout dimension, width:	350 mm
Cutout dimension, length:	350 mm
Vertical adjustment:	vertically adjustable upper section
Length:	332 mm
Width:	332 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
System:	vertical

Coverage features

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	95 mm
Length of cover:	95 mm
Frame material:	ABS
Cover locking:	placed
Load class:	K 3 (EN 1253-1)
Rim length:	132 mm
Rim material:	132 mm
Upper section material:	ABS
Odour trap:	included