


Light liquid trap DN 100, Slotted grating, with odour trap



Article information

Item no.: 51101
 GTIN: 4026092029763
 Price group: 10

Advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	yes
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm backwater:	1
Mechanical backwater flaps:	2

General characteristics

Standard:	EN 1253-3
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Backwater protection:	Type 5

Dimensions

Vertical adjustment:	30 - 90 mm
Net weight:	2,37 kg
Gross weight:	2,69 kg
Cutout dimension, width:	250 mm
Cutout dimension, length:	400 mm
Installation depth:	216 - 276 mm
Vertical adjustment:	vertically adjustable upper section
Length:	320 mm

Width:	243 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Material of drain body:	Polymer
Coverage features	
Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	188 mm
Length of cover:	188 mm
Load class:	K 3 (EN 1253-1)
Rim length:	200 mm
Rim material:	200 mm
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	yes
Odour trap:	included